

Self Assembly Filter Unit Kit Systems



AEKIT: registered trade mark of la fonte srl



AGITATION FILTRATION
& PURIFICATION
FOR PLATING INDUSTRY

lafonteTM.eu

KIT standard version

KCT Precoat tank version



ADVANTAGES:

- Improved flow distribution
- Fast and Easy Assembly
- Prompt delivery time
- Low cost
- Rapid swing lid closure system
- Quick change filter element

TECHNICAL FEATURES:

- PP Solid construction
- T max: 70°C (w/o PVC hoses)
- Magnetic drive pump
- Discs and cartridges version
- Filtration and Purification

CARTRIDGES FILTER UNITS

All models available with pre coat tank version "KCT"	Pump	KW	Pump		Cartridges - n° x l"
			Qmax l/h	* Pump filter l/h Q max	
Mod.					
KIT 3C2	MPPO51	0,12	3000	2500	3 x 20
			3500	3000	
KIT 7C2	KC6 PP	0,35	6600	5000	7 x 20
			7500	6000	
KIT 12C2	KC8 PP	0,75	12000	10000	12 x 20
			14500	12000	
KIT 15C2	KC11 PP	1,5	17000	15000	15 x 20
			21000	18000	
KIT 15C3	DB15 PP	2,2	30000	24000	15 x 30
			32000	25000	

DISCS FILTER UNITS

All models available with pre coat tank version "KCT"	Pump	KW	Pump		Surface area - A = m ²
			Qmax l/h	* Pump filter l/h Q max	
Mod.					
KIT 31D2	MPPO51	0,12	3000	2500	0,9
			3500	3000	
KIT 7D2	KC6 PP	0,35	6600	5000	2,15
			7500	6000	
KIT 12D2	KC8 PP	0,75	12000	10000	3,3
			14500	12000	
KIT 15D2	KC11 PP	1,5	17000	15000	4,6
			21000	18000	
KIT 15D2	DB15 PP	2,2	30000	24000	4,6
			32000	25000	



50 Hz

60 Hz

* It changes according with position of filter unit respect process tank